

Technical Data Sheet

SealGreen SCR1600 Professional Coatings Remover

SealGreen's most-asked-for product, SCR1600, continues to impress contractors with its ease of use and powerful removal properties. With three times the coverage rate of traditional petroleum removers, SCR1600 effectively removes multiple layers of topical sealers, acrylics, enamels, urethanes, latex, some epoxies, and other single-component coatings. Made with soybeans, SCR1600 is a safe, low-odor, non-caustic, green coating remover. As a leading innovator in green cleaning products, SealGreen introduced SCR1600 as a soy based paint remover, and changed the industry. SCR1600 is 100% biodegradable, practically odorless, and is safe for your hands, your work, and your customers.

Coverage:

Coverage per square foot varies depending on type and age of coating, number of layers and method of application. Horizontal: Average coverage is 125 sq ft per gallon (max 200 sq ft per gallon) Vertical: Average coverage is 75 sq ft per gallon

Test Area:

Due to variances in surfaces and conditions, always test in a small, inconspicuous area before using on complete project.

Application:

Apply a thick layer of SCR1600 by pouring, brushing, squeegee, thick nap roller, or commercial airless sprayer. Applying too thin will cause SCR1600 to dry out before removal is complete. Use a scraper to check if the coating is softened down to the surface. If not, wait longer and recheck. When the coating is completely softened, remove with a scraper.

Clean Up:

Use **SealGreen Oil Cleaner Degreaser** and a scrub brush, mop, or power washer to clean remaining thin residue. Remove excess coating(s) and SCR1600 before using a power washer for final cleaning. Allow surface to dry before further preparations.

Usage Tips from the Pros:

- For large application areas, use a professional airless sprayer or a 4-stage HVLP sprayer.
- For tough coatings or numerous layers, use a notched ½" squeegee or ¼" gauge rake. Square footage will be greatly reduced.
- When used outdoors, cover with a 2mil or thicker plas-

tic to help keep SCR1600 wet and working.

Biodegradable:

Meets or exceeds ASTM standards

Precautions:

Concrete surfaces may darken with use of SCR1600. Protect plants and vegetation with a plastic drop cloth. Always use care to prevent overspray from getting on surfaces other than the one being prepped or cleaned.

Warnings:

May cause skin irritation. May cause eye irritation. May cause respiratory irritation or may cause drowsiness and dizziness. May be harmful if swallowed. This product contains a chemical known to the state of California to cause birth defects or other reproductive harm. Keep out of reach of children.

Flash Point :

Above 200°F (93.3°C)

pH Level:

8.1 pH of 1/10 wt/wt solution in soft water

VOC (Volatile Organic Compounds):

49%, 4.249 lb/g, 509 g/l California and OTC Compliant

Ingredients:

N-Methyl Pyrrolidone, Dibasic Ester LVP, Soy Ester, Proprietary Thickening and Surfactant Blend

Safe for Use On:

Concrete, masonry, wood, and metal

Do Not Use On:

PVC, drywall, limestone, plastic, veneer, terrazzo tile, or rubber

For More Information Contact:

ReUse Concrete Sealing Specialists, LLC
16072 Foster St, Overland Park, KS 66085
913-681-3451 - www.sealgreen.com