

# Safety Data Sheet | 05/01/2014

# **Brick and Stone Sealer™ Concentrate**

SDS Preparation Date: 05/01/2014

This SDS adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries.

## SECTION 1. PRODUCT AND COMPANY INFORMATION

Manufacturer: ReUse Concrete Sealing Specialists LLC Tel.: (9130861-3451, Toll Free: (800)

997-3873 - www.SealGreen.com

**Chemical Family:** Water Based Siloxane Emulsion Concentrate.

**Trade Name:** SealGreen Brick and Stone Sealer

CAS #: Not Issued
CHEMICAL FORMULA: Confidential

## 24 Hour Emergency Phone Number CHEMTREC 800-424-9300

NOTE: Emergency telephone numbers are to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure, or accident involving chemicals. All non-emergency questions should be directed to customer service.

## **SECTION 2: HAZARDS IDENTIFICATION**

INGREDIENTS	CAS NUMBER	% BY WT*
- Dimethyl, Methylhydrogen siloxane	68037-59-2	20.0-40.0
- N-Octyltriethoxysilane	2943-75-1	20.0-40.0
- Trace Chemicals		<1.0
- Water	007732-18-5	Balance

<sup>\*</sup> The concentrations shown in the substance list are maximum or ceiling levels (weight %) to be used for calculations for regulations.

Per Environmental Protection Agency (EPA) Method 24 (7/1/91), Determination of Volatile Matter Content, this product has volatile solvents content (VOC) of <200 g/L. VOC Compliant.

## **SECTION 3 - HAZARD IDENTIFICATION**

NFPA 704 CODES: 0=Minimal, 1=Slight, 2=Moderate, 3=Serious and 4=Severe

HEALTH (BLUE) FLAMMABILITY (RED) REACTIVITY (YELLOW) CLOTHING
NFPA: 1 NFPA: 0 NFPA: 0 NFPA:
HMIS: 1 HMIS: 0 HMIS: 0 HMIS: PP = B

## **ACUTE EFFECTS OF OVEREXPOSURE:**

- EYE: Mildly irritating to the eyes.

SKIN: No skin irritation expected. May aggravate existing dermatitis.
 INHALATION: Breathing mist may cause mild irritation to upper respiratory tract.

- INGESTION: None known. Do not take internally.

CHRONIC EFFECTS OF OVEREXPOSURE: Repeated prolonged contact may produce irritation.

OTHER HEALTH EFFECTS (MEDICAL CONDITIONS GENERALLY AGGREVATED BY EXPOSURE): People with sensitive skin can experience aggravated skin irritation. No other known applicable information.

## **SECTION 4 - FIRST AID MEASURES**

**EMERGENCY FIRST AID PROCEDURES:** 

EYE: Immediately flush eyes with running water for at least 15 minutes. If irritation or adverse

symptoms develop, seek medical attention.

- SKIN: Minimal effect on contact, if irritation occurs wash skin with soap and water. If irritation or

adverse symptoms continue, seek medical attention.

- INHALATION: Remove to fresh air.

- INGESTION: Do not take internally. Drink large quantities of milk or water. Do not induce vomiting. Seek

medical attention if stomach upset occurs.

## **SECTION 5 - FIRE FIGHTING MEASURES**

Brick and Stone Concentrate does not support combustion and is not considered a fire or explosive hazard. When involved in a fire, it may emit vapors containing the siloxane containing materials, carbon oxides and silicon dioxide. These materials should be considered irritants. In addition, the silicon dioxide dust has a PEL of 6 mg/m3 and a ACGIH Total Dust of 10 mg/m3. It is possible that Brick and Stone Concentrate can create SiO2 dust levels greater than these PEL and AVGIH limits when decomposed in a fire or explosion. For these reasons, fire fighters should wear self-contained breathing apparatus and full protective clothing. Heated closed containers may burst due to steam pressure. Cool containers with water.

## **SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Contain spills immediately with inert material to prevent waterway entry. Transfer liquids and solid diking materials to suitable containers for recovery or disposal.

## **SECTION 7 - HANDLING AND STORAGE**

Handle in a well ventilated area. Maintain positive pressure in interior of occupied buildings during exterior application and close fresh air intakes in area of application. Avoid inhaling vapors and mists, and getting in eyes, on skin or on clothing. Wash hands and other contaminated areas thoroughly with soap and water after handling this product and before eating or smoking. Wash contaminated clothing and equipment thoroughly before reuse. Normal warehouse storage in a closed container is adequate. Storage temperature should be above freezing and below 120°F. Drain equipment and flush with water to clean. Shelf life is 18 months in original sealed container.

## SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Appropriate personal protective equipment necessary to prevent repeated or prolonged contact should be worn. Mechanical ventilation is recommended. Avoid breathing mist or vapors. Where high concentrations of mist occurs, a respirator with appropriate dust and mist removal capabilities is recommended. Eye protection, resistant clothing and resistant boots should be worn where spills or splashing can occur. Chemical splash goggles are recommended. A single prolonged skin exposure is not likely to result in skin irritation or absorption through the skin in harmful amounts. Wash contaminated clothing before reuse. Do not take internally. An eye wash station should be available.

## **SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE: Milk white
ODOR: Slight odor
pH: (Typical) 5
BOILING POINT, 760 mm Hg: 212PF, 100PC
VAPOR PRESSURE, at 20 °C: 17.5 mm Hg
LIQUID DENSITY: 1 g/cc

 SOLUBILITY IN WATER, by wt.:
 100 %

 SPECIFIC GRAVITY (H2O = 1):
 1.01

 VOC:
 <200 g/L</td>

VISCOSITY: Similar to water EVAPORATION RATE (Butyl Acetate = 1) Similar to Water

PHYSICAL STATE: Liquid

# **SECTION 10 - STABILITY AND REACTIVITY**

Brick and Stone Concentrate reacts with silica in concrete and masonry in the presence of ultraviolet light and moisture forming bonds with the substrate in normal use. The organic content of the aqueous mixture will react with bases, acids and oxidizers producing heat, polymers and oxidation by-products. Vaporization of small quantities of water controls any heat released. Atomization, vaporization or combustion forms aerosols which can carry siloxane containing materials, carbon oxides and silicon dioxide into the atmosphere. Hazardous polymerization will not occur.

## **SECTION 11 - TOXICOLOGICAL INFORMATION**

This product is known to be a mild eye and upper respiratory irritant. OSHA PEL and ACGIH TLV has not been established; however, the low vapor pressure of siloxane containing materials Brick and Stone Concentrate should produce air concentrations below expected exposure limits. The LD50 has not been determined, but should be relatively high based upon typical silicone toxicity. Do not take internally, avoid breathing mist and minimize eye and skin contact.

HEALTH HAZARD CATEGORIES: None of the product's ingredients are found on any lists of hazardous, carcinogenic or banned chemical agents or materials generated by them.

#### **SECTION 12 - ECOLOGICAL INFORMATION**

There is little or no risk to surrounding vegetation during application, and overspray on non-targeted areas can be easily removed with soap and water.

## **SECTION 13 - DISPOSAL CONSIDERATIONS**

The material is non-hazardous. Small quantities may be cleaned with soap and water, then flushed to a sanitary or industrial sewer. Absorbent material containing small amounts of the material may be disposed in appropriate landfills. Disposal of large quantities should comply with applicable disposal permits.

## **SECTION 14 - TRANSPORT INFORMATION**

DOT SHIPPING NAME (49CFR 172.101): None Regulated - DOT ID# (49CFR 172.101): None Regulated

- DOT HAZARD CLASS: Non Flammable Liquid, NOS

- MARKING: None Required
- LABEL: None Required
- PLACARD: None Required

#### **SECTION 15 - REGULATORY INFORMATION**

#### **FEDERAL**

This product is non-hazardous under the OSHA Hazard Communication Standard (29 CFR 1910-1200). All components are on the Confidential or Non-Confidential TSCA Inventory List. The ingredients of this product are listed on the Toxic Substances Control Act (TSCA) inventory and do not have special toxic substances warning requirements.

None of the components in this product require notification of the National Response Center under the Comprehensive Environmental Response Compensation, and Liability Act of 1980 (CERCLA) per 40 CFR 302.4. None of the components in this product require reporting under Superfund Amendment and Reauthorization Act of 1986 (SARA) Title III as emergency planning or release reporting per 40 CFR 355 (used for SARA 302, 304, 311 and 312). The components also do not require annual reporting as a toxic chemical under SARA Title III per 40 CFR 372 (for SARA 313). This product contains no chemicals subject to SARA Title III, Section -13, Part 372 reporting requirements.

#### **STATE RIGHT-TO-KNOW**

Under California Proposition 65, this product contains no listed substances at levels which would require a warning as a product known to cause cancer, birth defects or other reproductive harm.

Under the Massachusetts Right-To-Know Law, this product contains no listed substances at levels that require reporting per the Substance List.

Under the Pennsylvania Right-To-Know Law, this product contains no listed substances at levels that require reporting per the Hazardous Substance List.

## **SECTION 16 - OTHER INFORMATION**

n.e. = Not established; n.a. = Not applicable/ not available; n.d. = Not determined; TLV = Threshold Limit Value; PEL = Permissible Exposure Limit; OSHA = Occupational Safety and Health Administration: ACGIH = American Conference of Governmental Industrial Hygienists; LEL = Lower Explosive Limit; UEL = Upper Explosive Limit; ppm = parts per million; TSCA = Toxic Substances Control Act; SARA = Superfund Amendments and Reauthorization Act; Dot = Department of Transportation.

DATE: 5/1/14

SUPERCEDES: 10/1/13

This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license under valid patents.