

Girl Scouts locker and shower Areas – Safe Floor Wet or Dry

SealGreen was invited to solve a slippery floor when wet. Originally the locker room and the shower areas were coated with a sealer to protect the floor. Unfortunately, the sealer applied had a glossy finish and the girl scouts kept falling down because when the floor was wet it became very slippery in the shower areas and all other areas where the floor got wet.

Several floor vendors were invited to solve the problem, and the common answer was to remove the existing coating before it could be sealed with a non-slippery coating. Unfortunately, the customer did not have the funding for full removal of the old sealer and the application of a new coating.

[SealGreen Poly StepGuard with Antiskid](#) - Our solution was perfect for their budget and limited time to get the floor done. Since the [SealGreen Poly StepGuard with antiskid](#) only requires a good bondable surface we were able to wash/scrub the floor in one day and the second we apply two coats of the sealer. The key features of the sealer that the customer like:

- Quick installation – Minimum interruption – Application Video - <https://youtu.be/AzbGuLqxnRc>
- Available in Clear
- Non-Toxic, Minimal VOC's, Fumes, Odors
- Multi-Surface Solution for Concrete,
- Applicable to coated floors, ceramic tile, wood composites
- With antiskid to meet American Disabilities Act (ADA) requirements
- Ease of Application
- Single Component Product (No Mixing Req'd)
- Highly Water Resistant
- Does Not Mold or Mildew
- Protects Grout Lines
- Quick Drying Times
- Enhanced for UV Protection
- Does Not Attract Dirt
- Stain Resistant
- Easy To Clean

The [SealGreen Poly StepGuard with antiskid](#) solution provides a safe floor for waking barefooted, non-slippery when wet or dry, polyurethane durability for daily use, and the antiskid does not interfere with cleaning procedures when using mops, brooms, or other cleaning processes. And it does not change the look of the floor.

The long-term maintenance based on daily traffic will be every 4 to 5 years. The maintenance will require washing ([SealGreen Oil and Cleaner Degreaser recommended](#)) and re-application of the coating. No removal will be necessary.

Project Pictures:

Sample / Test Area



Washing and Scrubbing Floor:



Finish Floor – Sealed with SealGreen Poly StepGuard with Antiskid

