16072 Foster St. Overland Park, KS. 66085

913-681-3451

www.sealgreen.com

Technical Data Sheet

SealGreen Paver Cleaner

PRODUCT SPECIFICATIONS

GENERIC TYPE: Powder concentrate cleaner

GENERAL PROPERTIES: SealGreen Paver Cleaner, is a dual purpose product designed for the preparation of concrete or clay paver surfaces to clean dirt, mold and mildew, and prepare the surface for a sealer application. Secondly, the cleaner toughens the surface of the concrete by interacting with weak spots created by un-reacted calcium hydroxide. • Aggressive Cleaner • Strengthens surface • Biodegradable • Noncorrosive • Low Odor.

RECOMMENDED USE: Concrete or clay paver surface for the removal of dirt, mold and mildew, and preparation for SealGreen Paver Sealer.

NOT RECOMMENDED FOR: Coating removal including paint, sealer and other film forming products.

COLOR: White powder.

SPECIFICATION DATA SOLIDS CONTENT: Liberally apply allowing product to puddle.

STORAGE CONDITIONS: Temperature: 40-90°F

SHELF LIFE: Unopened Container 2 year, Opened Containers

2 months

AVAILABLE AS: 1 Pint, 1 Quart and 50 Lbs.

FLASH POINT: >212°F (100°C)

APPLICATION INSTRUCTIONS

Mix 1 pint container with 2.5 gallons of water, covers 500 square feet.

Mix 1 quart with 5.0 gallons of water, covers 1,000 square feet. Mix 50 pounds with water to desired strength, covers 20,000 square feet.

Mix until all powder is dissolved, warm water will help the powder to dissolve quickly.

CAUTION: Protect metal and glass. Rinse immediately if applied to glass or metal. **DO NOT ALLOW TO DRY**. Always wear safety gloves and safety glasses when working with any chemicals. Liberally apply the cleaner to the area. Apply with a pump sprayer soaking it well let sit for 10 minutes and rinse.

The longer it sits the more it cleans. Heavy dirt or mold areas require longer sitting time. Cleaner can be applied and left overnight. Cleaner will continue to work even if it dries.

For more cleaning power scrub the area with a rotary floor machine equipped with a nylon-grit scrub brush. Scrub in a pattern that causes the scrub brush to agitate the area at least two to four times.

When scrubbing is completed, do not rinse until the cleaner solution has been in contact with the concrete for at least 10 minutes.

Rinsing is extremely important and should employ generous amounts of clean water using a high pressure garden hose, power washer or agitation via a floor machine or a very stiff bristled brush. For inside applications remove rinse water with wet vacuum. Continue to rinse surface until vacuumed water is clear. An excellent indoor alternative for rinsing is the use of an automatic floor machine which applies rinse water, agitates the surface and vacuums the liquid. A pressure washer may be used on exterior substrates. Allow adequate time for the surface to dry before applying SealGreen Paver Sealer .

TECHNICAL SERVICE: Technical service engineers and chemists are available to answer questions on product performance, application methods and chemical composition. This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of ReUse Concrete Sealing Specialists, LLC.'s knowledge or obtained from sources believed by ReUse Concrete Sealing Specialists, LLC. does not assume any legal responsibility for use or reliance upon same. Tests should be carried out only by chemists or chemically qualified lab technicians. Before using any chemical, read its label and Material Safety Data Sheet.

How to Clean Pavers using SealGreen Paver Cleaner

Application Instructions

(Always follow the necessary safety precautions when applying products)

How to Clean the Pavers

Using SealGreen Paver Cleaner which is specially formulated to prepare wet-cast pavers prior to sealant application. The cleaner dislodges mold and releases agents and ground—in-dirt on wet cast pavers. SealGreen Paver Cleaner also conditions the paver for a sealer or color stain. This powerful formula works deep without discoloring or damaging the surface. SealGreen Paver Cleaner is not an acid that will etch the paver surface. It cleans evenly and enables sealants or color stains to better penetrate the material. SealGreen Paver Cleaner is totally environmentally safe.

- Mix the contents of the SealGreen Paver Cleaner container with the recommended amount of water per container instructions in a 5-gallon plastic pail.
 Mix until all cleaner is dissolved. DO NOT mix Paver Cleaner inside the pump sprayer.
- 2. Once the SealGreen Paver Cleaner is mixed completely, pour the cleaner into a garden pump sprayer. The sprayer should be equipped with a fan tip for better spray control. DO NOT spray on metal or glass because it will etch the surfaces permanently. Any metal or glass surface should be protected or shielded from cleaner. If the glass or metal is sprayed, immediately clean with water. DO NOT allow cleaner to dry on metal or glass.
- 3. Soak heavily areas of the pavers that have dirt or green mold growing or dark mold stains. It is recommended to apply cleaner heavily and allow to stay in place for 12 hours or overnight so it can penetrate deep into the mold. If cleaner dries the next day a light spray of the cleaner or water will regenerate the cleaner.
- 4. Rinse the cleaner with a pressure washer using no more than 3000psi and the green tip or a high-power garden hose nozzle. Cleaner can be rinsed to grass area. Cleaner will not harm vegetation.
- 5. Caution is necessary when rinsing pavers to not spray directly between the pavers because the sand between the pavers may come loose and may require more sand to be applied before sealing the pavers.
- 6. If Polymeric sand is used to repair open areas between pavers, please allow at least 12 hours for the polymeric sand to dry before applying sealer.
- 7. Allow the paver to dry for at least 12 hours before applying sealer.
- 8. Cleanup equipment and overspray with soap and warm water.