

STAMPED CONCRETE RESTORATION AND PRODUCTS REQUIRED

	Application	Sealer Removal	Surface Preparation	Antiskid	Color	Antiqueing Color	Sealer 1st Coat	Sealer 2nd Coat
Steps	Remove Old Sealer - Full Restoration	Yes						
1	CSR1600 Coating Remover	Yes						
1	1-1/4 inch roller cover	Yes						
1	2 inch trim brush	Yes						
1	Spike Shoes	Yes						
2	Surface Preparation - (Only if floor requires additional cleaning)							
	Color stain Primer Cleaner							
2	Oil Cleaner Degreaser		Option					
3	Antiskid							
3	Antiskid Black or White			Yes				
4	Color Stain				Yes	Option		
4	Paint Strainer				Yes	Yes		
4	2 inch trim brush				Yes	Yes		
4	Spike Shoes				Yes	Yes		
5	E15 Epoxy Sealer for stamped Concrete Kit - (E15 Kit Includes 1st and 2nd Coat)						Yes	Yes
5	1-1/4 inch roller cover						Yes	Yes
5	2 inch trim brush						Yes	Yes
5	Spike Shoes						Yes	Yes

	Application	Sealer Removal	Surface Preparation	Antiskid	Color	Antiqueing Color	Sealer 1st Coat	Sealer 2nd Coat
Steps	Surface Preparation - Wash Only		Yes					
1	Surface Preparation		Yes					
1	Color stain Primer Cleaner		Yes					
1	Oil Cleaner Degreaser							
2	Antiskid			Yes				
2	Antiskid Black or White			Yes				
3	Color Stain				Yes	Option		
3	Paint Strainer				Yes	Yes		
3	2 inch trim brush				Yes	Yes		
3	Spike Shoes				Yes	Yes		
4	E15 Epoxy Sealer for stamped Concrete Kit - (E15 Kit Includes 1st and 2nd Coat)						Yes	Yes
4	1-1/4 inch roller cover						Yes	Yes
4	2 inch trim brush						Yes	Yes
4	Spike Shoes						Yes	Yes

	Application	Sealer Removal	Surface Preparation	Antiskid	Color	Antiqueing Color	Sealer 1st Coat	Sealer 2nd Coat
Steps	Wash and Seal Only		Yes					

1	Surface Preparation		Yes					
1	Color stain Primer Cleaner		Optional					
1	Oil Cleaner Degreaser		Yes					
2	Antiskid			Yes				
2	Antiskid Black or White			Yes				
4	E15 Epoxy Sealer for stamped Concrete Kit - (E15 Kit Includes 1st and 2nd Coat)						Yes	Yes
4	1-1/4 inch roller cover						Yes	Yes
4	2 inch trim brush						Yes	Yes
4	Spike Shoes						Yes	Yes