



16072 Foster St. Overland Park, KS 66085 · 913-681-3461 · 800-997-3873 · info@sealgreen.com

Application Instructions - SealGreen Cure and Seal Concrete Sealer

Visit our YouTube Channel **SEALGREENTV** for videos on application instructions


It is best to apply on new concrete that has just been installed. The concrete should be green in color and wet. Poured concrete can be cured after it has set and a person can walk on it without any marks. If the concrete does not have any type of cure or sealer after 5-days of installation it is best to apply a full sealer like SealGreen Concrete Sealer with Salt Defense Technology or any of the other SealGreen sealers such Kennel Sealer, Polished Concrete Sealer or Garage Floor Sealer.

Normally only **ONE** application is necessary followed by spot applications over fast-absorbing or porous areas to completely cure and seal concrete walls, floors, driveways, etc. One gallon of mixed cure and seal will cover approximately 350-400 square feet.

Surface preparation: The surface should be green and wet from the initial installation and freshly poured.

Application Steps:

1. **Curing concrete surfaces** (broom finished and smooth hard trowel surfaces like driveways, sidewalks)
- Spray Cure/Seal Concrete Sealer using a **low-pressure hand-held sprayer using a fan tip** onto the concrete surface until it has a moist appearance if dry or is completely covered. Apply more SealGreen Cure and Seal Sealer to any areas that are absorbing quickly. **DO NOT** allow product to puddle on the surface. If sealer is over-



applied, a white powdery residue may appear. (If it is over applied and white stains appear wait until the concrete has cured for 5 days before washing the white stains).

2. Apply sealer with a steady even motion (**horizontal pattern/ then vertical pattern**). **DO NOT OVERAPPLY**. Video at: <https://youtu.be/RglZQ3Llk6Q>
3. A second **spot application** should be applied immediately after the first application to areas that dry faster than the majority of the surface, repeating step 2.
4. Do Not Allow overspray onto glass or metal as it will etch those materials. To clean overspray on glass, metal, plastic; use clean water immediately. Use water to clean tools. Wash hands with soap and water and use hand lotion.

General Application Tips

White Powdery Residue: Do not attempt to remove the white powdery residue which may result from over-application before 5 days after installation. After a couple of weeks, you can usually brush or wash the powder away. Any



16072 Foster St. Overland Park, KS 66085 · 913-681-3461 · 800-997-3873 · info@sealgreen.com

powdery residue will eventually wear off and go away. It results from the solids in the sealer that cannot be absorbed drying on the surface of the concrete.

Surface: If the SealGreen Cure and Seal is applied several days after the surface has hardened “**The Cleaner - The Better**” - Remove all loose material from the surface of the area to be sealed. Surface should be as clean as possible. Heavily soiled areas should be hosed off or power washed. We recommend the use of SealGreen Driveway/ Garage Cleaner to remove oil, dirt, mold, and other contaminants. **Do not use any petroleum-based cleaners when cleaning the surface.**

Sealer Application Equipment: A low-pressure hand-held pump sprayer with a fan tip is the quickest and easiest application equipment. **CAUTION:** Airless sprayers should not be used as they apply too much product which will result in the white powdery residue.

Ambient Temperature: SealGreen Cure and Seal Concrete Sealer is water-based; the temperature should be between 50 to 80 degrees 24 hours prior to and after the application to ensure that SealGreen Cure and Seal Concrete Sealer will not freeze in the cold weather or dry too quickly in hotter weather.

Poured Foundation/Walls: Start at the top and work your way down. This application requires two applications - one vertical and one horizontal.

**Rinse and recycle container when empty - Sealer is - non-toxic - non-hazardous - non-flammable
Keep out of reach of children - Use of safety glasses and plastic gloves is recommended when applying the
sealer - If splashed in eyes - wash with clean water
If swallowed, do not induce vomiting, but drink water for dilution
Wash your hands after using the sealer - Consult physician if required**