

Stamped And Decorative Concrete Restoration or Maintenance

START ALL OVER

REMOVE EXISTING SEALER

1. Remove sealer with SealGreen SCR1600 Coating Remover and wash surface with SealGreen Oil Cleaner Degreaser

- i. Product information: <http://sealgreen.com/scr1600-coatings-remover-with-oil-cleaner-degreaser/>
- ii. Application Video: <https://youtu.be/5fX72qJKA5o>

2. Allow surface to dry overnight

STAIN OVER EXISTING SEALER

WASH SURFACE

1. Wash surface with Color Stain Primer Cleaner

- i. Product information: <http://sealgreen.com/color-stain-primer-cleaner-for-water-based-color-stains/>
- ii. Application Video: <https://youtu.be/DmmMeDMFT1Y?t=45s>

2. Allow surface to surface to dry overnight

MAINTENANCE

APPLY PRIMARY COLOR

1. Re-apply color if needed - Main color - Choose from color chart

- i. Product information: <http://sealgreen.com/classic-color-stains/>
- ii. Application Video: https://youtu.be/CnT_pTsDvZs

2. Allow surface to dry for 24 hours minimum

ANTISKID - Recommended

Apply SealGreen Antiskid Black or White color

- i. Product information: <http://sealgreen.com/anti-skid-for-concrete-floors/>
- ii. Application Video: <https://youtu.be/DmmMeDMFT1Y?t=1m31s>

APPLY ANTIQUING COLOR

1. Re-apply color if needed - Antiquing color - Choose from color chart

- i. Product information: <http://sealgreen.com/color-chart-classic-series/>
- ii. Application Video: <https://youtu.be/9K3fZVakF8Y>

2. Allow surface to dry for 24 hours minimum

1ST SEALER COAT

1. Apply first coat of SealGreen E15 Epoxy Sealer

- i. Product information: <http://sealgreen.com/e15-epoxy-stamped-concrete-sealer/>
- ii. Application Video: <https://youtu.be/DmmMeDMFT1Y?t=1m52s>

2. Allow 24 hours before second coat is applied

2ND SEALER COAT

1. Apply second coat of SealGreen E15 Epoxy Sealer 24 hours after the first coat

- i. Product information: <http://sealgreen.com/e15-epoxy-stamped-concrete-sealer/>
- ii. Application Video: <https://youtu.be/DmmMeDMFT1Y?t=1m52s>

KEY NOTES:

Stain Over Existing Sealer

Because you are applying color stain over existing sealer some color peeling may occurred. This color can be easily fixed by repeating the steps in this process.

Maintenance

We recommend sealing your stamped concrete every 18 to 24 months to maintain your concrete looking good.

This document was created by:
SealGreen - ReUse Concrete Sealing
www.SealGreen.com
16072 Foster Street Overland Park, KS 66085
913-219-0013